Refrigeration & Air Conditioning Technology SECTION 4 ELECTRIC MOTORS UNIT 18: APPLICATIONS OF MOTORS PLEMAR MOTORS 2008 DELMAR MOTORS

Refrigeration & Air Conditioning Technology

UNIT OBJECTIVES

After studying this unit, the reader should be able to

- Identify the proper power supply for a motor.
- · Describe the application of three-phase versus singlephase motors.
- Describe other motor applications.
- Explain how the noise level in a motor can be isolated from the conditioned space.
- Describe the different types of motor mounts.
- Identify the various types of motor drive mechanisms.

DELMAR CENGAGE Learning

© 2008 Delmar, a part of Cengage Learnin

Refrigeration & Air Conditioning Technology

MOTOR APPLICATIONS


- The proper motor must be selected for proper system performance
- Motor must be able to function in the operating environment
- Motors are selected based on the power supply, system requirements, motor insulation type, motor class, bearing type and method of mounting the motor



© 2008 Delmar, a part of Cengage Learning

Refrigeration & Air Conditioning Technology THE POWER SUPPLY Provides correct voltage and sufficient current Motor nameplate provides power requirements including voltage, current, frequency, phase, locked rotor amperage and full load amperage Motors should operate within 10% of rated voltage Motors have a service factor (reserve horsepower) Frequency – number of cycles per second Power can be supplied as single or three phase

DELMAR CENGAGE Learning





Refrigeration & Air Conditioning Technology **ELECTRIC MOTOR WORKING** CONDITIONS · Working conditions determine the type of motor to be used Motors with centrifugal switches cannot be used in an explosive environment Sealed motors are used in dirty locations · Drip-proof motors should be used in wet locations

DELMAR CENGAGE Learning

Refrigeration & Air Conditioning Technology

INSULATION TYPE OR CLASS

- · Motors can safely operate up to a predetermined temperature
- · The insulation type determines the maximum allowable safe operating temperature
- The insulation type rating is determined by the allowable rise in temperature above the surrounding ambient temperature

DELMAR CENGAGE Learning


Refrigeration & Air Conditioning Technology


MAXIMUM WINDING **TEMPERATURES**

- Class A 221° F (105° C)
- Class B 266° F (130° C)
- Class F 311° F (155° C)
- Class H 356° F (180° C)



TYPES OF MOTOR BEARINGS
Bearing type is determined by load and acceptable noise levels
Sleeve bearings
- Used on light loads and low noise levels
- Lubricated with oil
Ball bearings
Noisier than sleeve bearings
- Lubricated with grease





DELMAR
CENGAGE Learning: 0 2008 Delmar, a part of Cengage Le

Refrigeration & Air Conditioning Technology MOTOR DRIVES · Connect the motor to the driven load · Transfers motor's power to the driven device · Direct drive - Motor shaft connected directly to the driven load - Driven load turns at the same speed as the motor - Uses belts and pulleys - Driven load can rotate at different speeds DELMAR CENGAGE Learning

Refrigeration & Air Conditioning Technology **UNIT SUMMARY**

- The proper motor must always be selected for proper system performance
- The power supply provides proper voltage and current capacity for proper motor operation
- Motors should operate within 10% of rated voltage
- Working conditions determine the motor to be used
- · Sleeve bearings operate quieter than ball bearings
- Application determines type of motor mount used
- · Motors can be used for direct or belt driven applications

23	DELMAR	